

# SPECIFICATIONS

## ARTICLE

Designation : **AlphaTec® 09928 glove**

Code bobet : **7060 : S.10**

Selling Unit : **pair**



Non-contractual pictures

## CHARACTERISTICS

### AlphaTec®

- Specifications : Fully coated, gauntlet
- Glove material : Neoprene coating, Cotton jersey liner. - Length : 450 mm.
- Possible harmful ingredients : Diphenyl guanidine and Diphenyl thiuram urea. (Only a very small number of users may be sensitised to any of these ingredients and hence may develop irritant and/or allergic reactions)
- Top quality neoprene coating : Protects against a wide range of oils, acids, caustics, alcohols and many solvents.
- Gauntlet option with quilted cotton liner, for use in both hot and cold temperatures. Permits intermittent handling in hot liquids up to 180°C and handling in cold temperatures down to -25°C.
- Guaranteed quality : caterorized in Category III (Protection against Mortal risks), good resistance to all mechanical hazards.
- Comfortable anatomical glove shape which follows the contours of the hand at rest. Improves dexterity and reduces hand fatigue.

## APPLICATIONS :

Chemicals handling, especially caustics and solvents, degreasing, metal fabrication, refining - oil & petrol, petrochemicals, plating

## RECOMMENDED STORAGE / APPLICATION :

- Keep out of direct sunlight, store in a cool and dry place and keep away from sources of ozone or ignition.
- Do not use against flames or at temperatures <-30°C or > 160°C.
- Poor versus oils, greases, hydrocarbons and most solvents.

## STANDARDS :

Complies with EU regulation 2016/425 relating to PPE (category III) and European standards:

- General requirements: EN ISO 21420:2020
- Chemical resistance: EN ISO 374-1 Type A AKLMPT
- Mechanical resistance: EN 388:2016 + A1:2018 3121B
- Heat and flame resistance: EN 407:2020 X1XXXX
- Microraganism: EN ISO 374-5:2016



0493 EN ISO 21420 :  
2020 Cat.III



EN388:2016 + A1:  
2018 - 3121B



EN ISO374-5:2016



EN ISO374-1:2016  
TypeA-AKLMPT



EN 407 : 2020  
X1XXXX