

# SPECIFICATIONS

## ARTICLE

Designation : **AlphaTec® 29500 glove**

Code bobet :

**8058 : S.8 black**

**8059 : S.9 black**

**8060 : S.10 black**

**8061 : S.11 black**

Selling Unit : **pair**

Non-contractual pictures



## CHARACTERISTICS

### AlphaTec®

- Specifications : Black unsupported, flocked cotton, neoprene/latex protective gloves, reverted lozenge finish. Cuff finish : straight.

- Length : 300 mm and thickness : 0.70 mm

- Possible harmful ingredients : Natural rubber proteins, Zinc diethyldithiocarbamate, Diphenyl-thiourea, Diphenylguanidine.(Only a very small number of users may be sensitised to any of these ingredients and hence may develop irritant and / or allergic reactions.)

- Medium-duty chemical protection with outstanding flexibility and ease of handling.

- Ideal for use in cold conditions - neoprene maintains its superb elasticity even at low temperatures.

- Neoprene formula. Protects against a wide range of acids, caustics, alcohols and many solvents.

- Superior flexibility : Contains natural rubber.

Much less tiring to the hands than other heavy-duty gloves.

- Flocklined in pure cotton : Soft, comfortable and absorbant.

## APPLICATIONS :

- Agriculture, chemical industry, refining - oil & petrol, cleaning, maintenance....

## RECOMMENDED STORAGE / APPLICATION :

- Keep out of direct sunlight, store in a cool and dry place, keep away from sources of ozone or ignition.

- Do not use against flames or temperatures < 0°C or > 100°C.

- Poor versus aromatic hydrocarbons, and chlorinated solvents.

## STANDARDS :

Complies with EU regulation 2016/425 relating to PPE (category III) and European standards:

- General requirements: EN ISO 21420:2020

- Mechanical risks: EN 388:2016 + A1:2018 X121A

- Chemical risks: EN ISO 374-1:2016 Type A AKLNPT

- Microorganisms: EN ISO 374-5:2016



0493 EN ISO 21420 :  
2020 Cat.III



EN388:2016 + A1:  
2018-X121A



EN ISO374-5:2016



EN ISO374-1:2016  
Type A - AKLNPT