

SPECIFICATIONS

ARTICLE

Designation : **Matte zinc galvanizing**

Code bobet : **3487**

Selling Unit : **Unit**



Non-contractual pictures

**CHARACTERISTICS**

- Long-lasting protection paint for the corrosion protection of metal parts in extreme environments (wet, saline, etc.)
- Protection of metal constructions, structures, pylons, piping, pipelines, tanks, reservoirs, boilers, fences...
- Forms a metallic appearance coating that is resistant to moisture and corrosion
- Fast drying : out of dust : 1 hour, recoverable : 12 hours
- High covering power, does not leak
- Enables to realize alterations after welding and after hot dip galvanizing
- Net volume : 400 ml
- Box of 12

TECHNICAL DATAS :

- Colour : grey
- Density at 15°C : 0.96
- Flash point : <21°C
- Temperature range : -30 to +500°C
- Gas : Butane/Propane

INSTRUCTIONS FOR USE :

- Thoroughly clean the surface to be treated, if necessary with the degreasing agent
- Remove rust with a wire brush
- Shake vigorously the aerosol before use
- Spray at 20/30 cm from the part to protect in cross layers.
- After use, purge the diffuser by applying a few pressures head down

APPLICATION :

Professional product in all industries and communities, public works companies, building, Metallurgical industries and boiler making, agricultural exploitations, port facilities, garages...