

# SPECIFICATIONS

## ARTICLE

Designation : **HARPON 326 latex glove**

Code bobet :

**24155 : S.6**

**23147 : S.7**

**23148 : S.8**

**23149 : S.9**

**23150 : S.10**

Selling Unit : **pair**

*Non-contractual pictures*



## CHARACTERISTICS

- Natural latex glove. Textile support interior. Reinforced grip on the hand. Blue color
- Guaranteed without silicone.
- Length: 32 cm and thickness: 1.35 mm
- Scallop cut cuff
- Excellent comfort of the textile support. Good thermal insulation. High resistance to abrasion.

## APPLICATIONS :

Handling of fatty foods, market gardening, oyster farming, fishing, fish-handling, handling fresh, fresh and slippery products

## RECOMMENDED STORAGE / APPLICATION :

- Store the gloves in their original packaging protected from light and away from sources of heat or electrical installations. It is recommended to test the gloves beforehand, as the actual conditions of use may differ from those of the "CE" type tests.
- The use of gloves is not recommended for subjects sensitized to natural latex, dithiocarbamates and thiazoles. Wear the gloves on dry, clean hands.
- Do not use the gloves in permanent contact with the chemical product for longer than the breakthrough time measured.
- In use with a dangerous liquid, turn the edge of the cuff upside down to prevent drops from falling on the arm.
- Allow the inside of the gloves to dry before reusing them. Before any reuse, check that the gloves do not show any cracks or tears.

## STANDARDS :

Compliant with EU Regulation 2016/425 relating to personal protective equipment (category III)

Complies with European standards:

- General requirements: EN ISO 21420:2020 (Dexterity: 5)
- Mechanical risks: EN 388:2016 + A1:2018 3141X
- Chemical risks: EN ISO 374-1:2016 Type B - KPT
- Thermal risks: EN 407:2020 X2XXXX

Complies with the French decree of August 5, 2020 relating to rubber materials and objects intended to come into contact with foodstuffs



0334

EN ISO 21420  
2020 Cat.III

EN388:2016 + A1:  
2018 - 3141X

EN ISO374-1:2016  
Type B - KPT

EN 407 : 2020  
X2XXXX