

SPECIFICATIONS

ARTICLE

Designation : **Partially threaded hexagon socket head capscrew DIN 912**


Code bobet : *See table below*

Selling Unit : **Hundred**



Non-contractual pictures

CHARACTERISTICS



Hexagon socket head capscrew, partially threaded

DIN 912

NFE 27-161

Stainless steel A2/S.S. 304

d (mm)	L (mm)	dk (mm)	H (mm)	P (mm)	PAS (mm)	Code Bobet
M3	30	5,32	2,86	2,5	0,5	2592
M3	40	5,32	2,86	2,5	0,5	6561
M4	30	6,78	3,82	3	0,7	2598
M4	35	6,78	3,82	3	0,7	2599
M4	40	6,78	3,82	3	0,7	2600
M5	30	8,28	4,82	4	0,8	2606
M5	35	8,28	4,82	4	0,8	2607
M5	40	8,28	4,82	4	0,8	2608
M5	50	8,28	4,82	4	0,8	2609
M5	60	8,28	4,82	4	0,8	2610
M6	35	9,78	5,7	5	1	2616
M6	40	9,78	5,7	5	1	2617
M6	50	9,78	5,7	5	1	2618
M6	60	9,78	5,7	5	1	2619
M6	70	9,78	5,7	5	1	7757
M8	40	12,73	7,64	6	1,25	2626
M8	50	12,73	7,64	6	1,25	2627
M8	60	12,73	7,64	6	1,25	2628
M8	70	12,73	7,64	6	1,25	2629
M8	80	12,73	7,64	6	1,25	2630

d (mm)	L (mm)	dk (mm)	H (mm)	P (mm)	PAS (mm)	Code Bobet
M10	50	15,73	9,64	8	1,5	2637
M10	60	15,73	9,64	8	1,5	2638
M10	80	15,73	9,64	8	1,5	2640
M12	60	17,73	11,57	10	1,75	2647
M12	70	17,73	11,57	10	1,75	2648