

# **SPECIFICATIONS**



## ARTICLE

<u>Designation :</u> Matador® HVL 3000 Extended slaughtering pistol <u>Code bobet :</u> 24800 <u>Selling Unit :</u> Unit



Non-contractual pictures

### **CHARACTERISTICS**



NEW MODEL WITH :

- PATENTED LOCKING SYSTEM and ERGONOMIC HANDLEBAR
- FAST, ANIMAL-FRIENDLY SPIT EVEN FOR LARGE ANIMALS
- SIMPLE MAINTENANCE
- OPERATOR-FRIENDLY, AUTOMATIC LOAD EXTRACTION

The MATADOR® is a captive bolt pistol using 27-caliber pyrotechnic charges. It is used for slaughtering animals such as large cattle and exceptional animals, as well as calves, cows and sheep. It consists of a barrel and a handle linked by a clevis joint.

Length: 330mm Spindle length: 93 mm Spindle diameter: 12 mm Diameter: d.60mm Weight: 2.86 kg Material: Steel Locking: Ball bearing Loads (cartridges): MATADOR® 27 gauge yellow, red, black (see LOADS paragraph)

Maximum authorized rate: 30 shots/hour Maximum number of shots: 40,000 shots Maximum service life: 3 years

For further information, please refer to the product leaflet.

### **CARTRIDGES :**

Loads to be used :



- BLACK LOADS :

\* Bobet code 24204 = box of 500

\* Reserved for large cattle over 700 kgs: bulls, exceptional animals, young cattle

 RED CHARGES : \* Code Bobet 24205 = box of 500
Standard model for general use on cows, calves, heifers and horses

- YELLOW LOADS:

\* Bobet code 24203 = box of 500

\*Recommended for slaughtering animals weighing less than 250 kg: sheep and goats

### **SAFETY AND MAINTENANCE :**

- You must have at least 2 guns on the slaughter site. Any gun that is faulty or shows signs of malfunction must be replaced immediately.

WARNING: Never remove a poorly exploded charge from the barrel by hand.

Never point the pistol at yourself or at another person, even if the pistol is not loaded.

### **MAINTENANCE :**

- Optional (sold separately): Tool kit for gun maintenance

### **IMPORTANT :**

As the components of the bolt gun, like the charges, are an integral part of the device, only those designed, tested, supplied or recommended by us may be used in our LE MATADOR® bolt guns (Inter-ministerial order of April 10, 1981 - J.O. of April 17, 1981 - chap. II - Art. 7 and chap IV - Art. 9 relating to approvals and conditions of use for this equipment). In the event of an accident, any deviation from the requirements set out in this decree, or any instructions for the use of this equipment, will incur the liability of those who take the initiative.

### **STANDARDS**:

Compliant :

- Complies with European Machinery Directive 2006/42/EC.
- Animal Welfare Regulation CE 2009/1099
- EN 15895 standard for hand-held propellant-operated tools
- General principles of machine safety EN ISO 12100

```
(6
```

Repère	Désignation	Qte	Code TERMET	Code BOBET
1	Anneau embout poignée	1	5907	21172
2	Embout	1	16	21171
3	Ressort marteau	1	21	7361
4	Ressort taquet	1	5795	20995
5	Taquet	1	18	10642
6	Ressort verouillage	1	3695	15642
7	Porte culot trèfle	1	10647	24802
8	Axe d'accouplement	2	34	7371
9	Cordon d'armement	1	41	7381
10	Marteau	1	19	7360
11	Poignée	1	3705	15640
12	Goupille	2	26	10644
13	Percuteur	1	24	7363
14	Bille de verrouillage	1	3698	15648
15	Chape de basculement	1	32	10647
16	Jonc de verrou	1	29	7368
17	Bague	1	10443	24805
18	Canon verrou	1	10685	24804
19	Joint de blocage	1	40	7380
20	Jonc tête de broche	1	30	7375
21	Broche HVL	1	10442	24801
22	Rondelle protection arrière bleu	1	1269	12417
23	Rondelle protection arrière brun	1	38	7377
24	Anneau élastomère (sachet de 11 pces)	1	9182	24855
25	Rondelle protection avant	2	39	7378
26	Disque étanchéité	1	65	7376
27	Rallonge HVL	1	10679	24803

