

SPECIFICATIONS

ARTICLE

Designation : **Rinsing nozzle 0° 1/4 female red protection**

Code bobet : **20620**

Selling Unit : **Unit**



Non-contractual pictures

CHARACTERISTICS

Accessory for central and satellite medium pressure installation (25-30 bars)

- Short adapter with nozzle and red EPDM rubber protection
- Flow : 40L/min
- Angle : 0°

See the list next page

ACCESSOIRES MOUSSE INOX

Pour installation centrale et satellite moyenne pression (25 - 30 bars)

- /// **Code 17581** : Adaptateur buse femelle ¼ 
- /// **Code 15871** : Adaptateur coupleur inox femelle ½
/// **Code 21883** : Adaptateur coupleur inox femelle ¼ 
- /// **Code 17870** : Adaptateur coupleur inox mâle ½ 
- /// **Code 15869** : Coupleur rapide inox femelle ½
Joint de rechange (le jeu de 2) code 20556 
- /// **Code 15868** : Coupleur rapide inox mâle ½
Joint de rechange (le jeu de 2) code 20556 
- /// **Code 20620** : Buse 0° - 40L/mn ¼ femelle + embout rouge 
- /// **Code 17814** : Buse 15° - 30L/mn ¼ femelle + embout vert 
- /// **Code 17167** : Buse 25° - 30L/mn ¼ femelle + embout bleu 
- /// **Code 17321** : Buse 25° - 60L/mn ¼ femelle + embout jaune 
- /// **Code 24825** : Lance rinçage 70 cm ¼ mâle 
- /// **Code 17139** : Lance mousse 22 cm ½ femelle 
- /// **Code 17168** : Lance mousse blanche ½ mâle 
- /// **Code 17583** : Protection buse ¼ bleue 
- /// **Code 17582** : Protection coupleur bleue 
- /// **Code 15999** : Vanne bleue mousse ½ femelle/femelle 
- /// **Code 17963** : Vanne bleue mousse ½ femelle/femelle complète 
- /// **Code 20806** : Vanne bleue mousse ½ femelle/femelle papillon 