

SPECIFICATIONS

**ARTICLE**Designation : **Ultrafit pre-molded ear plugs**Code bobet : **1618 : corded**Selling Unit : **Unit***Non-contractual pictures***CHARACTERISTICS**

- Thermoplastic elastomer plugs and PVC cord
- Triple flange design for comfortable and effective seal
- Easy to fit thanks to its long rod
- Soft and durable material
- One size for most ear canals
- Among the highest attenuations for this type of pre-molded plugs
- Easy to clean

DESCRIPTION :

The E-A-R Ultrafit roll-down ear plugs are designed to be put in the ear canal to reduce the exposure to hazardous noise.

APPLICATIONS :

The E-A-R Ultrafit pre-molded ear plugs are ideal to protect against moderate to high noise levels. They are especially adapted to noisy environments, whatever the frequencies, in industrial as well as during leisure time. Application : Food industries, Automotive, Chemicals and pharmaceuticals, Construction, Heavy works in civil engineering, Metallurgy, Textile industry, Wood industry

ATTENUATION :

- SNR = 29dB
- H = 29dB
- M = 27dB
- L = 24dB

- SNR = Attenuation Global Index (Single Number Rating) (value that is subtracted from the C-weighted noise level, L (C), to estimate the actual A-weighted noise level into the ear)
- H = High frequency attenuation value (value representing the expected attenuation of noise level with LC-LA = -2dB)
- M = Medium frequency attenuation value (value representing the expected attenuation of noise level with LC-LA = +2 dB)
- L = Low frequency attenuation value (value representing the expected attenuation of noise level with LC-LA = 10 dB)

PACKAGING :

100 pairs in a box

STANDARDS :

Complies with EU regulation 2016/425 relating to personal protective equipment
Compliant with European standard EN 352-2: 2002



706322